

Magnet-Mount Antenna Installation Instructions

1. Connecting directly to a phone


Attach your antenna to your cell phone using an adapter specific to your phone. The adapter (Sold Separately) connects the phone to the antenna cable and transfers power to and from the antenna. Adapter Guide at: www.wilsonelectronics.com

2. Connecting to a Wilson Electronics Signal Booster

The antenna cable attaches directly to the signal booster. Check your signal booster installation guide for specific instructions.

3. Installing the Magnet-Mount Antenna

Attach the Magnet-Mount Antenna to any metal area on top of the roof of the vehicle. The best location is clear of obstacles and as high on the vehicle as possible. Although small, the rare earth magnet is quite strong and won't fall off at high speeds. Make sure the area under the magnet is clean so as not to damage the vehicle's paint and to ensure a strong connection. Bring the cable into the vehicle through a door frame - the cable is protected by the door's rubber molding. Do not run the cable through a window because when the window is rolled up and the door is opened the antenna cable will be pulled - this is likely to destroy your antenna and/or scratch your paint. Connect the magnet-mount antenna cable to the adapter cable or signal booster.



1. Magnet-Mount Antenna

2. Mini Magnet-Mount Antenna

Magnet-Mount Antenna Installation Instructions

1. Connecting directly to phone

Attach your antenna to your cell phone using an adapter specific to your phone. The adapter (Sold Separately) connects the phone to the antenna cable and transfers power to and from the antenna. Adapter Guide at: www.wilsonelectronics.com

2. Connecting to a Wilson Electronics Signal Booster

The antenna cable attaches directly to the signal booster. Check your signal booster installation guide for specific instructions.

2. Installing the Magnet-Mount Antenna

Attach the Magnet-Mount Antenna to any metal area on top of the roof of the vehicle. The best location is clear of obstacles and as high on the vehicle as possible. Although small, the rare earth magnet is quite strong and won't fall off at high speeds. Make sure the area under the magnet is clean so as not to damage the vehicle's paint and to ensure a strong connection. Bring the cable into the vehicle through a door frame - the cable is protected by the door's rubber molding. Do not run the cable through a window because when the window is rolled up and the door is opened the antenna cable will be pulled - this is likely to destroy your antenna and/or scratch your paint. Connect the magnet-mount antenna cable to the adapter cable or signal booster.



1. Magnet-Mount Antenna

2. Mini Magnet-Mount Antenna

Technical Support

Additional help may be obtained by sending an email to tech@wilsonelectronics.com or by calling Toll-Free 866-294-1660 Monday through Friday between 7:00 AM and 6:00 PM Mountain Time. Wilson Electronics is closed Saturday, Sunday and Holidays.

90 Day Warranty

The Wilson Electronics Magnet-Mount Antenna is warranted for 90 days against defects in workmanship and/or materials and will be repaired or replaced, at the discretion of the manufacturer, to the original purchaser with dated sales receipt. The antenna and a copy of the receipt must be sent to the factory at purchaser's expense where it will be repaired or replaced and returned shipping paid. Warranty does not cover damages caused by abuse, misuse, negligence, improper installation, etc. These are considered to be avoidable circumstances. All Wilson Electronics warranties are limited to the specific Wilson Electronics product only and do not include phone, vehicle or other external product.



Part# 103019 Rev 08 / 12.01.10

Technical Support

Additional help may be obtained by sending an email to tech@wilsonelectronics.com or by calling Toll-Free 866-294-1660 Monday through Friday between 7:00 AM and 6:00 PM Mountain Time. Wilson Electronics is closed Saturday, Sunday and Holidays.

90 Day Warranty

The Wilson Electronics Magnet-Mount Antenna is warranted for 90 days against defects in workmanship and/or materials and will be repaired or replaced, at the discretion of the manufacturer, to the original purchaser with dated sales receipt. The antenna and a copy of the receipt must be sent to the factory at purchaser's expense where it will be repaired or replaced and returned shipping paid. Warranty does not cover damages caused by abuse, misuse, negligence, improper installation, etc. These are considered to be avoidable circumstances. All Wilson Electronics warranties are limited to the specific Wilson Electronics product only and do not include phone, vehicle or other external product.



Part# 103019 Rev 08 / 12.01.10

Magnet-Mount Antenna Installation Instructions

1. Connecting directly to phone


Attach your antenna to your cell phone using an adapter specific to your phone. The adapter (Sold Separately) connects the phone to the antenna cable and transfers power to and from the antenna. Adapter Guide at: www.wilsoselectronics.com

2. Connecting to a Wilson Electronics Signal Booster

The antenna cable attaches directly to the signal booster. Check your signal booster installation guide for specific instructions.

3. Installing the Magnet-Mount Antenna

Attach the Magnet-Mount Antenna to any metal area on top of the roof of the vehicle. The best location is clear of obstacles and as high on the vehicle as possible. Although small, the rare earth magnet is quite strong and won't fall off at high speeds. Make sure the area under the magnet is clean so as not to damage the vehicle's paint and to ensure a strong connection. Bring the cable into the vehicle through a door frame - the cable is protected by the door's rubber molding. Do not run the cable through a window because when the window is rolled up and the door is opened the antenna cable will be pulled - this is likely to destroy your antenna and/or scratch your paint. Connect the magnet-mount antenna cable to the adapter cable or signal booster.



1. Magnet-Mount Antenna

2. Mini Magnet-Mount Antenna

Magnet-Mount Antenna Installation Instructions

1. Connecting directly to phone

Attach your antenna to your cell phone using an adapter specific to your phone. The adapter (Sold Separately) connects the phone to the antenna cable and transfers power to and from the antenna. Adapter Guide at: www.wilsoselectronics.com

2. Connecting to a Wilson Electronics Signal Booster

The antenna cable attaches directly to the signal booster. Check your signal booster installation guide for specific instructions.

3. Installing the Magnet-Mount Antenna

Attach the Magnet-Mount Antenna to any metal area on top of the roof of the vehicle. The best location is clear of obstacles and as high on the vehicle as possible. Although small, the rare earth magnet is quite strong and won't fall off at high speeds. Make sure the area under the magnet is clean so as not to damage the vehicle's paint and to ensure a strong connection. Bring the cable into the vehicle through a door frame - the cable is protected by the door's rubber molding. Do not run the cable through a window because when the window is rolled up and the door is opened the antenna cable will be pulled - this is likely to destroy your antenna and/or scratch your paint. Connect the magnet-mount antenna cable to the adapter cable or signal booster.



1. Magnet-Mount Antenna

2. Mini Magnet-Mount Antenna

Technical Support

Additional help may be obtained by sending an email to tech@wilsoselectronics.com or by calling Toll-Free 866-294-1660 Monday through Friday between 7:00 AM and 6:00 PM Mountain Time. Wilson Electronics is closed Saturday, Sunday and Holidays.

90 Day Warranty

The Wilson Electronics Magnet-Mount Antenna is warranted for 90 days against defects in workmanship and/or materials and will be repaired or replaced, at the discretion of the manufacturer, to the original purchaser with dated sales receipt. The antenna and a copy of the receipt must be sent to the factory at purchaser's expense where it will be repaired or replaced and returned shipping paid. Warranty does not cover damages caused by abuse, misuse, negligence, improper installation, etc. These are considered to be avoidable circumstances. All Wilson Electronics warranties are limited to the specific Wilson Electronics product only and do not include phone, vehicle or other external product.



Part# 103019 Rev 08 / 12.01.10

Technical Support

Additional help may be obtained by sending an email to tech@wilsoselectronics.com or by calling Toll-Free 866-294-1660 Monday through Friday between 7:00 AM and 6:00 PM Mountain Time. Wilson Electronics is closed Saturday, Sunday and Holidays.

90 Day Warranty

The Wilson Electronics Magnet-Mount Antenna is warranted for 90 days against defects in workmanship and/or materials and will be repaired or replaced, at the discretion of the manufacturer, to the original purchaser with dated sales receipt. The antenna and a copy of the receipt must be sent to the factory at purchaser's expense where it will be repaired or replaced and returned shipping paid. Warranty does not cover damages caused by abuse, misuse, negligence, improper installation, etc. These are considered to be avoidable circumstances. All Wilson Electronics warranties are limited to the specific Wilson Electronics product only and do not include phone, vehicle or other external product.



Part# 103019 Rev 08 / 12.01.10